








Grant Optima™ stirred baths/circulators: operating temperature range				
<b>Key</b>  <ul style="list-style-type: none"> <li><span style="display: inline-block; width: 20px; height: 10px; background-color: #00FF00; border: 1px solid black;"></span> ambient +15 to 99°C</li> <li><span style="display: inline-block; width: 20px; height: 10px; background-color: #90EE90; border: 1px solid black;"></span> ambient +5 to 99°C</li> <li><span style="display: inline-block; width: 20px; height: 10px; background-color: #FFFF00; border: 1px solid black;"></span> 0 to 100°C</li> <li><span style="display: inline-block; width: 20px; height: 10px; background-color: #FFD700; border: 1px solid black;"></span> 0 to 120°C</li> <li><span style="display: inline-block; width: 20px; height: 10px; background-color: #FFA500; border: 1px solid black;"></span> 0 to 150°C</li> <li><span style="display: inline-block; width: 20px; height: 10px; background-color: #FF69B4; border: 1px solid black;"></span> 0 to 200°C</li> <li><span style="display: inline-block; width: 20px; height: 10px; background-color: #FF8C00; border: 1px solid black;"></span> -15 to 120°C</li> <li><span style="display: inline-block; width: 20px; height: 10px; background-color: #FF4500; border: 1px solid black;"></span> -15 to 150°C</li> <li><span style="display: inline-block; width: 20px; height: 10px; background-color: #FF00FF; border: 1px solid black;"></span> -15 to 200°C</li> </ul>				
	<b>GD100 digital</b> 	<b>GD120 digital</b> 	<b>GR150 digital high performance</b> 	<b>GP200 digital high performance</b> 
<b>Grant tanks</b> <b>Stainless steel (S) tanks*</b> 				
	<b>Model designation (tank + immersion thermostat)</b>			
<b>S5</b> - 5 L stainless steel	<b>GD100-S5</b>	<b>GD120-S5</b>	<b>GR150-S5</b>	<b>GP200-S5</b>
<b>S12</b> - 12 L stainless steel	<b>GD100-S12</b>	<b>GD120-S12</b>	<b>GR150-S12</b>	<b>GP200-S12</b>
<b>S18</b> - 18 L stainless steel	<b>GD100-S18</b>	<b>GD120-S18</b>	<b>GR150-S18</b>	<b>GP200-S18</b>
<b>S26</b> - 26 L stainless steel	<b>GD100-S26</b>	<b>GD120-S26</b>	<b>GR150-S26</b>	<b>GP200-S26</b>
<b>S38</b> - 38 L stainless steel	<b>GD100-S38</b>	<b>GD120-S38</b>	<b>GR150-S38</b>	<b>GP200-S38</b>
<small>*Minimum operating temperature without accessory cooling is ambient + 5°C (ambient + 15°C for Grant S5 tank)</small>				
<b>Plastic (P) tanks</b> 				
<b>P5</b> - 5L plastic	<b>GD100-P5</b>	<b>GD120-P5</b>	<b>GR150-P5</b>	<b>GP200-P5</b>
<b>P12</b> - 12 L plastic	<b>GD100-P12</b>	<b>GD120-P12</b>	<b>GR150-P12</b>	<b>GP200-P12</b>
<b>P18</b> - 18 L plastic	<b>GD100-P18</b>	<b>GD120-P18</b>	<b>GR150-P18</b>	<b>GP200-P18</b>